

Adjusted by:

E-mail:

Adjusted for:

Tel:

Date:

Total weight (g): **0**

The weight changes based on the choices made below.

Panthera X has the chassis and backrest made in carbon fibre and a rigid rear axle. The balance is adjusted by positioning the backrest in 4 different positions. Panthera X is delivered without anti-tip device and is intended for advanced users only. Max user weight is 100 kg for seat width 33-45 cm.

Save the guide to the "desktop" and open it with **Adobe Reader**, for best function Design your wheelchair by clicking in the circles in this guide. Blue, underlined text is clickable to show info or image. BB = seatwidth, HH= backrest height

Original design

Alternative options

Other options

[info](#)



1) Seat width (BB) Chassis [art.no.](#)

- 33 cm
- 36 cm
- 39 cm
- 42 cm
- 45 cm
- Clear



2) Backrest height 22-35 cm (HH) [art.no.](#)

- 22 cm
- 23 cm
- 24 cm
- 25 cm
- 26 cm
- 27 cm
- 28 cm
- 29 cm
- 30 cm
- 31 cm
- 32 cm
- 33 cm
- 34 cm
- 35 cm
- Clear



3) Balance [info](#)

- Position 1**
Most easy balanced
- Position 2**
Less easy balanced
- Position 3**
Medium balanced
- Position 4**
Least easy balanced
- Clear

The positioning of the backrest on the chassis affects the balance / COG of the wheelchair. "easy balanced" = easy to practice rear wheel balance. This can later easily be changed.



4) Castor [art.no.](#)

- 3" X (87 mm)
- Clear

- 90 mm S3 [art.no.](#)



5) Footrest

- [Footrest Alu X](#)
36004 BB
- Clear

- [Footrest Titanium](#)
36915BB
- [Footrest Titanium, extended, reinforced](#)
36006BB [needed for Freewheel](#)
- [Plastic plate for foot bow](#)
36010BB



7) Brake [art.no.](#)

- [One hand brake, right](#)
- Clear

- [One hand brake, left](#)



8) Rear wheel - without pushrim

- [24" Spinergy X](#) black spokes [art.no.](#)
- [24" Spinergy X](#) white spokes
- Clear

- [25" Spinergy X](#) black spokes
- [25" Spinergy X](#) white spokes
- [26" Spinergy X](#) black spokes
- [26" Spinergy X](#) white spokes

[Rear wheel sizes](#)

Tire -choose tire

- [Schwalbe One](#) 24", 25"
- Clear

- [Right Run](#) 24",25",26"
- [Marathon Plus](#) 24",25",26"

- [Rugged](#) 24"



10) Push rim

- [Aluminum X](#)
1904404 (5) (6) (x2) 24" (25") (26")
- Clear

- [Titanium](#) DD = Wheel diameter in inches
- 190DD11 x2
- [Paragrip](#)
- 19051DDBTx2
- [Tetragrip](#)
- 19052DDBTx2

- [Maxgrip](#) 24" (contains latex)
1903060 x2

Accessories



Side guard

[info](#) desired art

- [Carbon article number](#)

Clear



Side guard

- [Carbon, small cover art.no.](#)

Clear



Side guard

- [Carbon, largecover art.no.](#)



Cushion

- [X 5 cm](#)
- 47501BB

seat depth 40 cm

Clear

Wedge cushion

- [Wedge cushion](#)

57710BB



Arm hook

- [Arm hook X](#)

4200010

Clear



Transport protection

- [Housing](#)
- 9024009
- [Rear end](#)
- 9024012
- [Rear axle](#)
- 9024008



Other

- [Freewheel info](#)
- 2600102
- [Tube protection front](#)
- 9900252 (2 pcs)
- [Tube protection rear](#)
- .9900252 (1 pcs)


Set-up adjustments



Backrest angle

Note measure (A) for desired back rest angle
10-20 mm. Standard=15 mm

A= _____ mm



Footrest height

Note measure (A) for desired footrest height
Standard = 70 mm

A= _____ mm

Extra